

The following listing of claims sets forth the text and status of claims in the application:

**Listing of Claims:**

Claim 1 (previously amended) Method for treating optical signals from a source thereof, which comprises the steps of:

- (a) providing a movable diffractive optical element (MDOE) having a surface carrying a holographic diffraction grating including an array of facets, each of said facets carrying a diffraction grating(s) which are superimposed, each being angularly offset with respect to each other;
- (b) directing a source of input optical signal(s), each of said input signal(s) being associated with a given wavelength, onto said MDOE to generate output signal(s);
- (c) supplying one or more output station(s); and
- (d) moving said MDOE to distribute any said output optical signal(s) to any said output station(s).

Claim 2 (cancelled)

Claim 3 (previously amended) The method of claim 1, wherein said MDOE is provided as a magnet having said holographic diffraction grating attached thereto, and being magnetically coupled to a coil energizable for movement of said magnet and said diffraction grating.

Claims 4-16 (cancelled)

Claim 17 (previously amended) A system for treating optical signals from a source thereof, which comprises:

a source, a movable diffractive optical element (MDOE), and output station(s), wherein

- (a) said source carries input optical signal(s), each of said signal(s) being associated with a particular wavelength;
- (b) said movable diffractive optical element (MDOE) has a surface carrying a holographic diffraction grating including an array of facets, each of said facets carrying a diffraction grating(s) which are superimposed, each being angularly offset with respect to each other, said MDOE being positioned to intercept said input optical signal(s) for generating output optical signal(s)

and distributing any said output optical signal(s), to any said output optical station(s) and;

- (c) said output station(s) being positioned to receive said output optical signal(s) from said MDOE.

Claims 18-31 (cancelled) The system of claim 17, wherein said MDOE comprises a rotatable diffraction optical element (RDOE).

Claim 32 (previously amended) In a method for treating optical signals wherein optical signals provided by fiber optic cable(s) or laser diode(s) as input optical signals are distributed among output stations as output optical signals, each of said output stations comprising optical connector(s) positioned to receive said output optical signals, said optical connectors being selectively combinable to permit any combination of said output optical signals, the improvement which comprises the steps of:

- (a) providing a movable diffractive optical element (MDOE) having a surface carrying a holographic diffraction grating including an array of facets, each of said facets carrying a diffraction grating(s) which are superimposed, each being angularly offset with respect to each other;
- (b) directing said source of input optical signals onto said MDOE to generate output signals, each of said input signals being associated with a given wavelength; and
- (c) moving said MDOE to distribute any said output optical signals to any said output stations.

Claims 33-39 (cancelled)